



| A   | B | C  | D   | E   | E1 | F   | F1  | G   | m[kg] |
|-----|---|----|-----|-----|----|-----|-----|-----|-------|
| 170 | 5 | 94 | 158 | 5,5 | 8  | 105 | 105 | 135 | 3,64  |

|               |      |          |          |                            |       |         |                      |            |          |          |                            |       |         |                      |    |
|---------------|------|----------|----------|----------------------------|-------|---------|----------------------|------------|----------|----------|----------------------------|-------|---------|----------------------|----|
| <b>CE</b>     | IP66 | CLASS:F  |          |                            |       |         |                      | TYPE:FBC80 |          |          |                            | No:   |         |                      |    |
|               | S1   |          |          |                            |       |         |                      |            |          |          |                            |       |         |                      |    |
| 50Hz          |      |          |          |                            |       |         |                      | 60Hz       |          |          |                            |       |         |                      |    |
|               | U[V] | I[A] max | P[W] max | n[ $\text{min}^{-1}$ ] max | p[Pa] | LpA[dB] | Q[m <sup>3</sup> /h] | U[V]       | I[A] max | P[W] max | n[ $\text{min}^{-1}$ ] max | p[Pa] | LpA[dB] | Q[m <sup>3</sup> /h] |    |
| $\mu\text{F}$ | 1~1  | 230-277  | 0,12     | 28                         | 2950  |         |                      | 220-277    | 0,14     | 35       | 3450                       |       |         |                      |    |
|               | 3-Δ  | 200-303  | 0,14     | 30                         | 2950  | 60      | 62                   | 58         | 220-332  | 0,12     | 33                         | 3500  |         |                      |    |
|               | 3-Y  | 346-525  | 0,08     | 30                         | 2950  | 60      | 62                   | 58         | 380-575  | 0,07     | 33                         | 3500  | 72      | 71                   | 70 |

|                                |            |             |         |            |  |
|--------------------------------|------------|-------------|---------|------------|--|
| Designed by                    | Checked by | Approved by | Date    | Date       |  |
|                                |            |             |         | 23.05.2018 |  |
| Y3-80; Y3HE2-80; Y3PE80; AM_80 |            |             | FBC80   |            |  |
| Fremdbelüftung_FBC80           |            |             | Edition | Sheet      |  |
|                                |            |             |         | 1 / 1      |  |